



GREASE

Cartridge Range



Rock Oil 500g grease cartridges are suitable for grease guns (with an SR screw fit) allowing for accurate and clean lubrication of machinery with an achievable pressure of 400 bar. These four products cover a wide range of environments including machinery involved in heavy load conditions, high temperatures, and other automotive, bearing, and industrial applications.

<p>BLUE LITHIUM EP 2 SV</p> <p>PN. 67050</p> <p>Colour: Blue Thickener: Lithium Base Oil: 220 Temp Range: -20°C to +140°C Application: Cars, trucks, and machinery NLGI Classification: 2</p> 	<p>RED LITHIUM COMPLEX EP 2</p> <p>PN. 65102</p> <p>Colour: Red Thickener: Lithium Complex Base Oil: 150 Temp Range: -20°C to +150°C Application: Roller bearings in electric motors, cars, fans, and construction machinery NLGI Classification: 2</p> 	<p>LITHIUM MOLY EP 2</p> <p>PN. 65103</p> <p>Colour: Black Thickener: Lithium Base Oil: 180 Temp Range: -20°C to +140°C Application: Plain and roller bearings subject to heavy or shock loads NLGI Classification: 2</p> 	<p>LITHIUM EP 2</p> <p>PN. 65123</p> <p>Colour: Light Brown Thickener: Lithium Base Oil: 180 Temp Range: -20°C to +140°C Application: Cars, trucks and machinery NLGI Classification: 2</p> 
--	--	--	--